

WL2 Firewall™

Excellent purifying performance,
easy operation and stylish design



R600a gas

**Zero
environmental
impact**

Simply pure water for the workplace

With a choice of hot, cold, and ambient, the WL2 FW is the preferred solution for any small or medium size workplace looking for great tasting water, reliability and guaranteed quality.

Advanced technology

The WL2 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall™

Waterlogic's Firewall patented technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risks of cross-contamination.

Certified purity for peace of mind

The Firewall™ technology has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – no other water cooler features these standards of certification together. This means that Firewall technology delivers the safest water possible for the workplace.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and pathogens purifying the water up to 99.9999%, 100% of the time

Dispensing area suitable to accommodate sport bottles

Environmentally friendly refrigeration using R600a: naturally occurring refrigerant gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 10 - 30

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

349 mm/13.7" (W) x 1024 mm/40.3" (H) x 363 mm/14.3" (D)

Countertop:

349 mm/13.7" (W) x 473 mm/18.6" (H) x 363 mm/14.3" (D)

Dispensing area height

230 mm/ 9"

Weight (Hot and cold models)

Countertop: 20-24 KG/ ~44-52 lbs

Freestanding: 27-29 KG/ ~59-61 lbs

Standard filtration supplied

Carbon

Storage capacity

Hot tank: 1.5 litres (0.4 US gal.)

Cold tank (Freestanding): 4 litres (1.06 US gal.)

Cold tank (Countertop): 2 litres (0.53 US gal.)

Drip tray capacity

360 ml

Compressor

Compressor (R600a 1/8HP) 230V/50Hz

Water temperatures settings

Cold: 3°/ 5°/ 7° C (default 5°C)

Hot: 85-87°C/ 185-189°F (default 85°C)

Tested and certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Call us today

UK www.waterlogic.co.uk

+ 44 (0) 333 323 2307

info@waterlogic.co.uk

Ireland www.waterlogic.ie

+ 353 1 466 0133

info@waterlogic.ie

USA and Canada www.waterlogicausa.com

+ 1 402 905 2001

customerservice@waterlogicausa.com

Rest of the World www.waterlogic.com

+ 353 1 293 1960

exportsales@waterlogic.com

For more information, visit www.waterlogic.com