

WL H1 Bar - Series E

A high capacity, elegant and compact unit for the HORECA sector



Electronic model



**R290 gas available on 230v models only*

Designed with the hospitality sector in mind

WL H1 Bar - Series E efficiently addresses high volume for cold, ambient and sparkling water even at peak times, for fast bottle and carafe filling. A unique and smart design for a features-rich worktop dispenser.

Leading technology

The WL H1 Bar - Series E features two core technologies:



Ice Bank cooling system

The Ice Bank cooling technology is paramount to the HORECA needs, where large quantities of consistently ice-cold water are required.



Performance filtration

Professional grade filters are used to satisfy the need for high water consumption, addressing colour, taste and odour, for great tasting, crystal-clear water.

Professional water dispensing for commercial environments

WL H1 Bar - Series E is the recommended solution for catering and intensive use environments such as bars, restaurants, cafeterias, conference centers.

Features

- Clean design and external surfaces in stainless steel
- Adjustable drip tray height to easily fill different sized bottles and carafes
- Three water dispensing options, cold, ambient and sparkling, with professional grade carbonator in stainless steel
- Practical taps allow three bottles to be filled at the same time
- Electronic model features portion control function to preset the volume of water dispensed
- Eco-sustainable refrigeration using R290 natural gas, for low environmental impact
- Energy saving, standby function reduces overall power consumption by 75% compared to full operation mode (available on electronic models only)
- Optional UVC light (available on electronic models only)



Tap model

Model	Tap	Electronic	Tap	Electronic
Dispensing capacity	80 L/h		150 L/h	
Water options				
Dispensing operation	Manual mechanical taps	Push buttons	Manual mechanical taps	Push buttons
Weight	35 kg		46 kg	
Dimensions	345 mm 592 mm 580 mm	345 mm 592 mm 555 mm	488 mm 589 mm 580 mm	488 mm 589 mm 555 mm
Dispensing area	203-242 mm 280-332 mm	238-277 mm 315-372 mm	202-240 mm 279-336 mm	237-275 mm 314-370 mm
Portion control	n/a	Yes	n/a	Yes
Energy saving	n/a	Yes	n/a	Yes
Compressor	(R290 gas) 230v - 50Hz (1/5 HP)		(R290 gas) 230v - 50Hz (1/5 HP)	
	(R134a gas) 115v - 60Hz (360 kcal/h)		(R134a gas) 115v - 60Hz (360 kcal/h)	
Water temperature	5°-12°C/41°- 54°F		5°-12°C/41°- 54°F	
UVC	n/a	Yes	n/a	Yes

Tested and certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice.

Contact the export team today

Waterlogic Trading Ltd
+ 353 1 293 1960
exportsales@waterlogic.com

For more information, visit www.waterlogic.com